

Two Hold Pipe Straps

Part No.	Dimension		Bolt Size (In.)	Material Size (In.)	Design Load (lbs.)*		Torque (ft./lbs.)	Product Weight / Piece (lbs.)
	A (In.)	B (In.)			Type 1	Type 2		
PS050	0.840	4.840	1/2	1/4 x 1-5/8	135	50	4	
PS075	1.050	5.050	1/2	1/4 x 1-5/8	135	50	4	
PS100	1.315	5.315	1/2	1/4 x 1-5/8	135	50	4	
PS150	1.900	5.900	1/2	1/4 x 1-5/8	135	50	4	
PS200	2-3/8	6.375	1/2	1/4 x 1-5/8	135	50	4	0.14
PS250	2-7/8	6.875	1/2	1/4 x 1-5/8	135	50	4	0.17
PS300	3-1/2	7.500	1/2	1/4 x 1-5/8	135	50	4	0.20
PS350	4	8.000	1/2	1/4 x 1-5/8	135	50	4	0.33
PS400	4-1/2	8.500	1/2	1/4 x 1-5/8	175	60	4	0.23
PS500	5-9/16	9.563	1/2	1/4 x 1-5/8	175	60	4	0.39
PS600	6-5/8	10.625	1/2	1/4 x 1-5/8	175	60	4	0.39
PS800	8-5/8	12.625	1/2	1/4 x 1-5/8	225	125	4	0.51
PS1000	10-3/4	15.750	5/8	1/4 x 1-5/8	225	125	10	0.77
PS1200	12-3/4	16.250	5/8	1/4 x 1-5/8	225	125	10	0.83
PS1400	14	18.000	5/8	3/8 x 1-5/8	250	150	10	1.25
PS1600	16	20.000	5/8	3/8 x 1-5/8	250	150	10	1.43
PS1800	18	23.000	5/8	3/8 x 1-5/8	250	150	10	1.60

*Design loads shown represent a 3:1 safety factor

Notes:

Bolts and Channel Nuts are sold separately.

When bolting onto 1-5/8" or 1-1/2" channel a 1-1/4" long bolt is required.

